PRODUCT SPECIFICATION	
CPU	32-bit Centrality Atlas III,400 MHZ
Chipset	SiRFStar III high-sensitivity GPS receiver (WAAS-enabled), 20 Channels
Memory	ROM type: Flash EEPROM 64 MiB RAM type: SDRAM 64 MiB
Display	5.0 inch TFT touch screen Resolution: 480 x 272 pixels
Bluetooth	Version 2.0+EDR, version 2.1 ready Class 2, 10 meters Operation frequency 2.4GHz-2.48GHz ISM
FM Transmitter	Operation frequency band: FM 87.6-107.9MHz Max. transmitting power 3.1 nW EIRP
Operating System	Windows CE 5.0
Media Formats	Picture: JPG Audio: Windows Media® Audio Standard (WMA), MP3 and WAV Video: WMF, ASF, Mpeg 4, MPEG, Flash
Interfaces	USB2.0 High speed 3.5mm Stereo headphone jack MMC, SD card slot, capacity up to 4GB (card not icluded)
Power Supply	Rechargeable Lithium-Ion Battery 1600mAH Car charger, Input: 10-24V, 1.3 A Max, Output: 5V, 1A
Dimensions	121 mm x 80 mm x 14.5 mm (W x H x D)
Mass	210 gr.
Menu Langauge Support	Chinese, English, German, Spanish, Portugese, French, Serbian etc.
Speakers	Internal, 1.5 W
Other Features	Support different map: Route66, I-GO, Ndrive etc.
Environment Conditions	Tempreature: Operation 0~40°C, Storage 0~60°C Humidity: Operation 0~90%, Non-condense and Storage 0~90%, Non-condense
Certification & Regulation	FCC, CE